



Type Approval Certificate

This is to certify that the undernoted product(s) has/have been tested with satisfactory results in accordance with the relevant requirements of the Lloyd's Register Type Approval System.

Manufacturer	Kobelt Manufacturing Co. LTD
Address	8238 - 129th Street, Surrey, V3W 0A6, Canada
Place of Production	Kobelt Manufacturing Co. LTD 8238 - 129th Street, Surrey, V3W 0A6, Canada
Type	Hydraulic Cylinders
Description	2510, 2510B, 2512, 2512B, 2514, 2514B, 3512, 3512B, 3515, 3515B, 3518, 3518B, 4516, 4520, 4524
Trade Name	25, 25B, 35, 35B, 45
Application	Marine and offshore use in Steering Gears
Specified Standard	Lloyds Register Rules and Regulations for Classification of Ships, July 2025 Lloyds Register Rules and Regulations for Classification of Special Service Crafts, July 2025 Lloyds Register Rules and Regulations for Classification of Mobile Offshore Units, July 2025 Lloyds Register Rules and Regulations for Classification of a Floating offshore Installation at a Fixed location, July 2025
Ratings	25 & 25B: Bore Diameter in inches: 2.50

71 Fenchurch Street, London, EC3M 4BS, United Kingdom

Jenny Wilson

Engineering - Machinery Principal Specialist
to Lloyd's Register EMEA
A member of the Lloyd's Register group

Lloyd's Register Group Limited, its affiliates and subsidiaries and their respective officers, employees or agents are, individually and collectively, referred to in this clause as 'Lloyd's Register'. Lloyd's Register assumes no responsibility and shall not be liable to any person for any loss, damage or expense caused by reliance on the information or advice in this document or howsoever provided, unless that person has signed a contract with the relevant Lloyd's Register entity for the provision of this information or advice and in that case any responsibility or liability is exclusively on the terms and conditions set out in that contract.



Type Approval Certificate

Rod Diameter in inches: 1.25
Pin Diameter in inches: 1.25
Stroke in inches: 10, 12 and 14
Maximum Working Pressure: 1600psi (110.3 bar)
Relief Valve Pressure: 2000psi (137.9 bar)
Test Pressure: 3000psi (206.8 bar)

35 & 35B:
Bore Diameter in inches: 3.50
Rod Diameter in inches: 1.75
Pin Diameter in inches: 1.75
Stroke in inches: 12, 15 and 18
Maximum Working Pressure: 1600psi (110.3 bar)
Relief Valve Pressure: 2000psi (137.9 bar)
Test Pressure: 3000psi (206.8 bar)

45:
Bore Diameter in inches: 4.50
Rod Diameter in inches: 2.25
Pin Diameter in inches: 2.00
Stroke in inches: 16, 20 and 24
Maximum Working Pressure: 1600psi (110.3 bar)
Relief Valve Pressure: 2000psi (137.9 bar)
Test Pressure: 3000psi (206.8 bar)

This certificate is not valid for equipment, the design, ratings or operating parameters of which have been varied from the specimen tested. The manufacturer should notify Lloyd's Register EMEA of any modification or changes to the equipment in order to obtain a valid Certificate.

Previous Version: LR2065289TA

The Design Appraisal Document LR2684378TA and its supplementary Type Approval Terms and Conditions form part of this Certificate.

71 Fenchurch Street, London, EC3M 4BS, United Kingdom

Lloyd's Register Group Limited, its affiliates and subsidiaries and their respective officers, employees or agents are, individually and collectively, referred to in this clause as 'Lloyd's Register'. Lloyd's Register assumes no responsibility and shall not be liable to any person for any loss, damage or expense caused by reliance on the information or advice in this document or howsoever provided, unless that person has signed a contract with the relevant Lloyd's Register entity for the provision of this information or advice and in that case any responsibility or liability is exclusively on the terms and conditions set out in that contract.